
KRESCENT

defining texture through the negative space of the crescent



Luxurious from every angle, DuChâteau Wall Coverings offer refined sophistication and depth to any surface with clean lines and geometric-inspired elegance.

WALL COVERINGS



SPECIFICATIONS & COLORS

♦ SPECIES (s)

Defined per Finish (see color chart)

♦ CUT PATTERN

Curved

♦ THICKNESS

*1-3/16 inches (30.16 mm)

◆ TILES/BOX

16

◆ COLORS

13 Available

GRADE

Aged Character with Knots

♦ COVERAGE/TILE

*1.29 sf. (0.120 m²)

♦ WEIGHT/TILE

*3.95 lbs. (1.79 kg) • Walnut *4.15 lbs. (1.88 kg) • White Oak

♦ INSTALL DIRECTION

Horizontal, Vertical or Diagonal

♦ FIRE RESISTANT

Optional "A Rating" Fire Retardant

SURFACE TEXTURE (ST)

Defined per Finish (see color chart)

COVERAGE/BOX

*20.64 sf. (1.92 m²)

♦ WEIGHT/BOX

*67.05 lbs. (30.41 kg) • Walnut *70.25 lbs. (31.86 kg) • White Oak

♦ INSTALLATION

Construction Glue & Fine Needle Nails

Weight, coverage and dimensions may vary depending on finish and the natural expansion and contraction of wood.





Product Sample Disclaimer

Created to be a one-of-a-kind piece of nature's artistry, each and every Duchâteau' wood product carries distinct variations in finish, patina, texture, grain and overall character that create the unique diversity and natural elegance of our wall coverings. It is virtually impossible to capture – in a small sample – the entire range of color variation and character that will be present in the wall covering you will receive. To better understand the unique look of a DuChâteau finished wall covering in your space, we recommend consulting your sales representative for more details.

Installation and Performance Disclaimer

Environmental conditions, such as exposure to light, and fluctuations in temperature and humidity, will greatly affect product performance from initial installation throughout its life. Refer to our website for installation guidelines or see your local sales representative for more information on proper steps and specific environmental conditions to successfully install, care for and ensure the lifelong performance of your wall covering.